

Envirotac II.comTM

Acrylic Polymer
info@envirotac.com

The Ultimate Protection Against Dust & Erosion

Intermediate Bulk Container (IBC) Tote/Drum
NMFC# 1546240 Liquid Plastic Material Freight Class: 60
Harmonized Code/Schedule B Commodity Number: 3905210000
(Polymers of vinyl acetate in an aqueous dispersion)
Gross Weight*: 2,600 lb (1,180 kg)/500 lbs (230 kg)
Net Contents*: 250 - 275 gallons (947 ltrs)/55 gallons (208 ltrs)
Dimensions*: 40x48x36 in. (100x120x90 cm)/23x35 in. (59x89 cm)
*specifications are approximate

Environmental Products and Applications, Inc.
73-710 Fred Waring Drive, Suite 220
Palm Desert, CA 92260
Toll Free (888) 674-9174 Fax (760) 779-1815

Features: Envirotac II will resist UV rays, water, and alkaline breakdowns for long periods of time. It is Environmentally Safe, noncorrosive, nonflammable, and ecologically safe. It will not leach, no tracking, easily mixed with water, safe and clean to use. Proven to be one of the most cost effective means in comparison to other materials and water trucks.

These instructions are for heavy traffic application

- Step 1: Select your desired area
- Step 2: Spray Envirotac II at a rate of 1 gallon concentrate mixed with 8 parts water.
- Step 3: Do not let cure, immediately start to blade.
- Step 4: Blade area to 3 to 4 inches depth
- Step 5: Spray at a rate of 1 gallon concentrate/5 parts water.
- Step 6: Do not let cure, immediately start to roll and compact
- Step 7: Roll the entire area
- Step 8: Strong compaction must be achieved.
- Step 9: Spray at a rate of 1 gallon concentrate/4 parts water.
- Step 10: Let final application cure (Est. 12-24 hrs.)



Step One



Step Two



Step Three



Step Four



Step Five



Step Six



Step Seven



Step Eight



Step Nine



Step Ten